



**TABELLA COMPARAZIONE FILETTATURE DI USO PIU'
COMUNE**

Grandezza pressacavo <i>Size cab/egland</i>	Diametro di filettatura imbocco "M" e "F" / <i>Diameter of thread hub M and F</i>							
	Standard	Equivalenti coniche			Equivalenti cilindriche			
	GAS UNI ISO 7/1	GK GAS UNI 6125	NPT ANSI ASME BI.20.1	GAS UNI ISO 228/1	N.P.S.M.	PG DIN 4030	ISOMETRICA	BET BS31
3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	PG9-PG11	16	5/8"
1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	PG13,5-PG16	20	3/4"
3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	PG21	25	1"
1"	1"	1"	1"	1"	1"	PG29	32	1 1/4"
1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	PG36	40	1 1/2"
1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	PG36- PG42	50	2"
2"	2"	2"	2"	2"	2"	PG48	63	2 1/2"
2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	/	75	3"
3"	3"	3"	3"	3"	3"	/	90	/
4"	4"	4"	4"	4"	4"	/	/	/

comm@antideflagrantigce.com